

# High Temperature Kinematic Viscosity Bath

- Wide range of bath temperatures to choose from.
- Digital microprocessor temperature control for accurate, easy-to-read bath temperature.
- Precise temperature control and stability +/- 0.01°C.
- Built-in safety features for over temperature and low liquid level conditions.
- Large illuminated viewing window.
- Completely self-contained – no additional heating or cooling units needed.
- Worldwide electrical compatibility.
- Meets all ASTM requirements for D445.
- One year warranty on all parts and labor.

Temperature Range	<b>Model KV803:</b> 30°C to 100°C (86°F to 212°F) <b>Model KV804:</b> 30°C to 150°C (86°F to 302°F)
Testing Capacity	Seven (7) samples
Bath Size	4.5 gallons 17.0 liters
Viewing Window	11 x11 inches 28 x28 cm
Temperature Control	+/- 0.1°C Digital +/- 0.01°C Analog
Temperature Sensor	Stainless steel thermistor and RTD
Heating Capacity	1500 watts
Dimensions	16W x 20D x 18H inches 40.5W x 45D x 51H cm
Safety Features	Low level warning Very low level shut down High temperature limit
Electrical	115 VAC / 20 Amps or 220 VAC / 10 Amps Single-Phase 50 or 60 Hz
Cabinet Material	Stainless steel and durable thermoplastic

